

# Canon



## CORPORATE SOLUTIONS



**imageRUNNER®**  
5000E / 5000EN

To maintain the highest levels of productivity in today's business environment, organizations must do more with less. Introducing the imageRUNNER 5000E/5000EN digital imaging systems. Delivering exceptional productivity, ease-of-use, and reliability, the imageRUNNER 5000E/5000EN models are multifunction solutions that large workgroups and corporate departments can depend on.

The imageRUNNER 5000E/5000EN models build on the benchmark reputation of previous Canon imageRUNNER product offerings. They deliver a fast speed of up to 50 pages per minute, high image quality, network integration, and optional finishing capabilities. High-yielding supplies and consumables help reduce downtime and lower operating costs. These features, plus a multitude of convenience and productivity attributes, make the imageRUNNER 5000E/5000EN devices economical multifunction solutions for busy departments.

# SPECIFICATIONS



## MAIN UNIT

Type:	Monochrome Digital Multifunction Imaging System
Copying Method:	Laser Dry Electrostatic Transfer
Developing System:	Dry Monocomponent Toner Projection
Memory:	Standard 192MB RAM
Hard Disk Drive:	5.1GB (Max. Capacity: Approximately 4,000 Originals)
Copy/Print Speed (Letter):	Up to 50 ppm
First-Copy Time:	3.8 Seconds or Less from Platen Glass 5.1 Seconds or Less from ADF
Warm-Up Time:	5 Minutes or Less
Acceptable Originals:	Sheets, Books, 3-Dimensional Items (Up to 4.4 lb.)
Max. Original Size:	11" x 17" (Ledger)
Max. Copy Size:	11" x 17" (Ledger)
Min. Copy Size:	4" x 5-7/8"
Max. Mail Boxes Supported:	100
Max. Copy Reservation:	5 Jobs
Scan Resolution:	600 x 600 dpi
Copy Resolution:	1200 x 600 dpi (Interpolated)
Print Resolution:	2400 x 600 dpi (Interpolated)
Halftone:	256 Gradations of Gray
Duplexing:	Standard Automatic Trayless Duplexing
Magnification Reduction/Enlargement:	25% to 400% in 1% Increments
Multiple Copies:	1 to 999
Standard Paper Supply:	Dual Front-Loading Trays (1,500 Sheets Each) Dual Front-Loading Cassettes (550 Sheets Each) 50-Sheet Stack Bypass (Total: 4,150)
Paper Weights:	17 lb. to 24 lb. Bond (550-Sheet Cassettes) 17 lb. Bond to 110 lb. Index (Stack Bypass, 1,500-Sheet Drawers)
Dimensions (H x W x D):	44-3/4" x 25-3/8" x 29-1/4" (1136mm x 643mm x 743mm)
Weight:	Approximately 462 lb. (210kg)
Power Requirements:	120V AC, 60Hz, 15A
Power Consumption:	1.5kW (Max.)
Toner:	Estimated Yield: 33,000 Impressions (at 6% coverage)

## ACCESSORIES

<b>Automatic Document Feeder (Standard)</b>	
Acceptable Originals:	Statement to 11" x 17"
Capacity:	100 Sheets (Letter/20 lb.)
Acceptable Paper Weight:	13 lb. to 32 lb. Bond
Original Replacement Speed:	Up to 50 Sheets/Minute (Letter)
<b>Print Features (5000EN Only)</b>	
CPU:	Canon Custom Processor
Memory:	192MB(Std./Max.)—Shared
Hard Disk:	5.1GB—Shared
PDL Support:	PCL 5e/6, PostScript® 3™ Emulation
Interface Connections:	10/100Base-TX (RJ-45)
Network OS:	Windows 2000/XP/Windows Vista® Windows Server 2003/2008 Macintosh® OSX/Citrix Metaframe
<b>Finisher-F1 E (Optional)</b>	
Number of Trays:	2 Trays
Tray Capacity	
Top Tray:	1,000 Sheets (Letter, Statement-R) 500 Sheets (Letter-R, Legal, 11" x 17") Offset Stacking: Max. 30 Sets (All Sizes)
Lower Tray:	1,000 Sheets (Letter, Statement-R) 500 Sheets (Letter-R, Legal, 11" x 17") Offset Stacking: Max. 30 Sets (All Sizes)
Staple Position:	1-Any Corner 2-Side Margin
Max. Stapling Capacity:	50 Sheets (Letter, Statement) 30 Sheets (Letter-R, Legal, 11" x 17")
Power Source:	Directly from Main Unit
Dimensions (H x W x D):	41-3/8" x 26-3/8" x 24-1/4" (1052mm x 669mm x 614mm)
Weight:	Approximately 70.5 lb. (32kg)

## Puncher Unit-B1 E (Option for Finisher-F1 E)

Max. Paper Weight:	17 lb. Bond to 110 lb. Index
Punch Types:	2-Hole, 3-Hole (Auto Change) 3-Hole (Letter, 11" x 17") 2-Hole (Legal, Letter-R)
Punch Dust Stock:	Approximately 3,000 Sheets
Power Source:	Directly from Main Unit
Dimensions (H x W x D):	34-7/8" x 3" x 24-1/4" (886mm x 75.5mm x 614.4mm)
Weight:	11.9 lb. (5.4kg)

\* NOTE: FACTORY CERTIFIED MODEL - This FACTORY CERTIFIED MODEL has been thoroughly inspected and cleaned. It has had a prescribed number of parts replaced so as to ensure operation and quality to Canon standards. This model has been assigned a new model name and serial number, may incorporate new features and/or functions, and has had its meter reset to zero. This model contains new, refurbished, and/or recovered parts and fully meets the original equipment manufacturer's quality and operational standards for this FACTORY CERTIFIED machine.



1-800-OK-CANON  
www.usa.canon.com

Canon U.S.A., Inc.  
One Canon Plaza  
Lake Success, NY 11042

As an ENERGY STAR® Partner, Canon U.S.A., Inc. has determined that the imageRUNNER 5000EN model meets the ENERGY STAR guidelines for energy efficiency. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. PostScript is a registered trademark or trademark of Adobe Systems Incorporated in the United States and/or other countries. Macintosh is a trademark of Apple Inc. Windows and Windows Vista are registered trademarks of Microsoft Corporation in the United States and/or other countries. CANON, IMAGERUNNER, and the GENUINE logo are registered trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. IMAGEANYWARE is a trademark of Canon. All other referenced product names and marks are trademarks of their respective owners and are hereby acknowledged.  
Specifications and availability subject to change without notice.  
©2009 Canon U.S.A., Inc. All rights reserved.

